

DESCRIPTION

These blocks have the same frame and are similar to our regular A1400 series blocks, except they have extra wide sheaves and a large throat.

They are ideal for reconductoring or any job that requires an unusually large throat for passing swivels, splices, bulges, etc.

A dependable conductor stringing block designed for hard service and ease of operation.

Made entirely from high-strength aluminum alloy permanent-mold castings that are designed with large fins, yet have voids where possible for reducing weight.

Streamlined, all edges are contoured and corners are rounded. There are no projections to injure workers or obstruct passage when raising or lowering block.

Convenient, frames have hand holds for carrying and handline hook. The top yoke swings clear, and is secured by, and easily operated by a captive, non-loseable safety-locking handle.

The throat is both wide and high, with smoothly contoured edges. Swivels, etc., pass through block without danger of jamming.

A choice of self-lubricating bronze, ball, or tapered roller bearings is offered. The tapered roller bearing absorbs side loads (THRUST), and assures free-turning sheaves when either stringing or sagging.

A choice of conductive-type Neoprene liner, or Urethane liner is offered, and is extra.




MODEL NO. A1428C

**SHOWN WITH
URETHANE LINER**

A1400 Series


LARGE THROAT STRINGING BLOCKS



MODEL NUMBER	SHEAVE DIAMETER	CONDUCTOR CAPACITY		WORKING LOAD POUNDS	WEIGHT POUNDS
		WITHOUT LINERS	WITH LINERS		
A1408C	8"	3"	3"	3,000	14
A1410D	10"	3"	3"	3,500	20
A1415C	15"	3"	3"	4,000	29
A1418C	18"	3"	3"	4,000	36
A1422C	22"	3"	3"	4,000	50
A1428C	28"	3"	3"	8,000	74

Load ratings are based on average lead angle when conductors are strung under normal stringing conditions and are conservative.

SPECIFICATIONS EXTRA LARGE THROAT STYLE				
BLOCK NO.	A	B	C	D
A1410B	7-1/4"	2-1/8"	4"	17"
A1410C	7"	2-1/2"	4"	17"
A1412A	9"	2-1/8"	9"	19"
A1412C	9"	9"	9"	19"
A1415B	11-7/8"	4"	4"	22"
A1416A	14"	3-5/8"	14"	23-1/2"



SEE SUSPENSION FITTING ATTACHMENTS BELOW.

SUSPENSION FITTING ATTACHMENTS

12	14	14A	15	16	20
MODEL NUMBER	DESCRIPTION			LOAD CAPACITY	LOAD CAPACITY
12	Safety Ball Hook			4,000	2,000
14	Plain Ball Clevis			4,000	
14A	Plain Ball Clevis with Captive Pin				
15	Y-Ball Clevis			20,000	
16	Oval Eye Ball			15,000	
20	Socket Eye			20,000	11,000



