

DESCRIPTION

These blocks are high grade units that will give many years of hard service. They are compact and light weight and convenient for linemen to carry.

Safe, strong and practical. They offer a selection of forged steel fittings that meet the lineman's needs.

The frames are aluminum-alloy and have smoothly contoured edges that will not damage the rope.

The sheaves are made from elastomer material that is very strong and practically unbreakable, and the rope groove is deep and the radius fits the rope.

A choice of high-grade ball bearings or self-lubricating bronze bearings is offered.

NOTE:
All hooks are standard with a safety latch.



Series A150 and A156

LINEMEN'S HANDLINE BLOCKS

STANDARD THREADING STYLE

MODEL NUMBER	TYPE OF FITTING	SHEAVE SIZE	ROPE SIZE	WORKING LOAD POUNDS	WEIGHT POUNDS
A151-E	Swivel Eye	2-1/2"	1/2"	450	1"
A151-1	No. 1 Hook with Rib Back	2-1/2"	1/2"	450	1-1/2"
A151-B	No. 2 Hook with Safety Latch	2-1/2"	1/2"	450	1-1/2"
A151-C	No. 2 Hook with Eye & Safety Latch	2-1/2"	1/2"	450	1-1/2"
A151-6	No. 5 Swivel Hook with Safety Latch	2-1/2"	1/2"	450	1-1/2"
A151-3	No. 3 Safety Snap Hook	2-1/2"	1/2"	450	1-1/2"
A151-4	No. 4 Super Safe Hook (4")	2-1/2"	1/2"	450	1-1/2"
S151D (Steel)	State Number of Hook	2-1/2"	1/2"	450	1-1/2"
A156-E	Swivel Eye	4"	3/4"	900	3-1/2"

NOTE: Always state article number and type of hooks and bearings wanted when ordering.

SUSPENSION FITTING ATTACHMENTS						
No. 1	No. 2	No. 2-E	No. 3	No. 4 & No. 4-A	No. 5	No. 5
Large Hook with Ribbed Back	Hook with Safety Latch	Hook with Safety Latch and Eye	Snap Hook	Super-Safe Hook (4") & (5")	Swivel Hook with Safety Latch	Loose Swivel Hook with Safety Latch

NOTE: The hooks listed above are available individually or as components of blocks.

HOOK NUMBER	DESCRIPTION	WORKING LOAD POUNDS	THROAT CAPACITY
1	A very useful block hook. It has a loose swivel connection, and may be folded over and attached to a pin-type insulator, or other anchorage.	450	2-1/4"
2	Regular style plain hook with safety latch.	450	
2-E	Regular style plain hook with safety latch and eye/ring.	450	
3	A safe, small hook used in a block or separately on a handline.	450	
4	An all-purpose hook. It may be attached to endless handline or other rope without removing knots, etc., quickly. It is safe and must be manually removed.	450	
4-A	An all-purpose hook. It may be attached to endless handline or other rope without removing knots, etc., quickly. It is safe and must be manually removed.	450	

