



Heavy -duty blocks designed for stringing four (or two) conductors simultaneously with a single pulling line.

Constructed with tubular steel frames and axles, steel center drum, aluminum alloy sheaves, and tapered roller bearings.

Blocks may also be converted into off-set configuration three bundle blocks.

A choice of conductive-type Neoprene liner, or Urethane liners are offered.

CROSSHEAD SHOWN IS NOT SUPPLIED WITH BLOCK.

S1200 Series

STANDARD FRAME STYLE --- HEAVY DUTY --- FOR USE WITH FOUR CONDUCTORS

FOUR-BUNDLED CONDUCTOR BLOCKS

MODEL NUMBER	SHEAVE DIAMETER	BOTTOM OF GROOVE DIAMETER	CONDUCTOR CAPACITY		WORKING LOAD POUNDS	ULTIMATE STRENGTH POUNDS	WEIGHT POUNDS
			WITHOUT LINERS	WITH LINERS			
S1220B4	20"	16"	2"	1-3/4"	7,000	21,000	248
S1222D4	22"	18"	2"	1-3/4"	8,000	24,000	296
S1222C4	22"	18-1/4"	3"	3"	8,000	24,000	296
S1228D4	28"	24"	2"	1-3/4"	8,000	24,000	325
S1228C4	28"	24"	3"	3"	8,000	24,000	325
S1236D4	36"	30"	2-1/8"	1-11/16"	12,000	30,000	750
S1236I4	36"	30"	2-3/8"	2"	12,000	30,000	760

Load ratings are based on average lead angle when conductors are strung under normal stringing conditions and are conservative. Blocks should be grounded. Reasonable caution should be used to prevent accidents caused by over-loading and abuse.

For current prices call (918) 756-3640 or E-mail at campbellspecialty@att.net

CONVERSION KITS	
Kit for converting one two-bundle block into two single blocks. Kit consists of: (A.) Two stub axles with one nut and cotter. (B.) Two socket eyes. (C.) Conductor guards and hardware.	Kit for converting two single blocks into one two-bundled block. Kit consists of: (A.) One long axle. (B.) One steel center drum. (C.) One set (2) roller bearings.
Kit No. 20 for 20" Blocks	Kit No. 24 for 20" Blocks
Kit No. 21 for 22" Blocks	Kit No. 26 for 22" Blocks
Kit No. 22 for 28" Blocks	Kit No. 27 for 28" Blocks
Kit No. 23 for 36" Blocks	Kit No. 28 for 36" Blocks

